


ProMinent® DULCOFLEX Series

Overview: DULCOFLEX DFDU



The DULCOFLEX DFD is a hose pump designed for pressures up to 232 psi and flow rates up to 160 gpm. The unique shoe design is made of steel for smoother and cooler compression. The DFD uses safe DulcoLube oil for the shoe lubrication. With suction lifts up to 29 feet, the DULCOFLEX DFD is a great choice for difficult pumping applications.

Feature & Benefits

- Sizes: 25, 32, 40, 60, 70, 100mm
- Flows to 160 gpm
- Suction lifts up to 29 ft.
- Disaster proof hose connections
- DulcoLube food grade glycerin lubricant
- Designed heat sink fins for cooler operation
- Steel shoes for a smoother and cooler compression
- Run dry capabilities

DULCOFLEX DFDU Capacities

Capacity Data						
	DFDU25	DFDU32	DFDU40	DFDU60	DFCU70	DFDU100
DFDU Series						
Compression	Shoe	Shoe	Shoe	Shoe	Shoe	Shoe
Connection	1"	1 1/2"	1 1/2"	2 1/2"	2 1/2"	4"
Capacity gal/rev	0.08	0.16	0.37	0.85	1.76	5.28
Max. Flow GPM	5.2	9.6	20.4	42.4	88	160
Max. Pressure Reinforced Hoses	232 psi	232 psi	232 psi	232 psi	232 psi	232 psi

All models are available with one of the following reinforced hoses: Natural Rubber, Buna, EPDM, Hypalon